

shown in Matte White
with 56" Gray Ash blades



Alessandra



Minimal form with maximum efficiency. With a wide range of blade sizes, the Alessandra can accommodate any space. This thoughtfully crafted and versatile fan will complement any aesthetic and improves the health and comfort of any room. Highly customizable, the Alessandra is available in five different body finishes, seven blade options, and even an option with a CCT light kit as the Alessandra-LK. Suitable for wet locations. Backed by a limited lifetime warranty, our fans are of the highest quality and will dutifully perform for years to come. Constructed of cast aluminum and heavy stamped steel, the Alessandra has a limited lifetime warranty.

Product Features



DC
Motor



Wet
Location



Silent



Remote
Control



Optional
Wall Control




30° Slant
Ceiling Canopy



60° Cathedral
Ceiling Canopy



Unipack
Shipping*



shown in Matte Black with 72" Matte Black blades

shown in Brushed Nickel with 42" Brushed Nickel blades

shown in Matte Black with 56" Barn Wood blades

shown in Matte White with 42" Walnut blades

shown in Brushed Brass with 56" Barn Wood blades

shown in Textured Bronze with 42" Walnut blades

shown in Matte White with 56" Gray Ash blades

ALESSANDRA

FINISH AND BLADE OPTIONS

SKU#	AK-XXXX-XXX-XX (Model+Finish+Blade+Diameter)	
Standard Finishes	Brushed Brass Brushed Nickel Matte Black Matte White Textured Bronze	BRBR BN BK MWH TB
Blade Finishes	Barn Wood Brushed Nickel Matte Black Matte White Gray Ash Walnut	BW BN BK MWH GA WN
Fan Diameter	42 inches / 107 cm 56 inches / 142 cm 72 inches / 183 cm	42 56 72

TECHNICAL SPECS

Fan Diameter	inches: 42, 56 or 72 centimeters: 107, 142 or 183
Blade Material	ABS
Overall Drop	8 inches / 20 cm + downrod length
Fan Weight	17 lbs
Downrods Lengths	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183 <i>Field cuttable. Non-threaded</i>
Downrod Diameter	1 inch
Voltage	110 or 220
Motor Type	DC
Environment	Wet location. All weather blade system. Neither outdoor coastal, saltwater nor chlorine compatible
Ambience	Silent
Safety Certification	ETL / CETL
Warranty	Limited Lifetime

NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA

Fan Diameter	42 inch / 107 cm	56 inch / 142 cm	72 inch / 183 cm
RPM (Low / High)	50 / 192	50 / 138	50 / 107
CFM (Low / High)	1349 / 5741	2436 / 7259	4208 / 8869
Watts (High)	35.97	34.79	34.37
CFM/Watt (High)	168	232	307
Blade Pitch	13°	13°	13°

STANDARD EQUIPMENT

One downrod of 10 inches / 25 cm

Slant ceiling canopy for up to 30°

Black 6-speed RF remote control with reverse



ACCESSORIES





White wireless Decora-style, 6-speed, wall control




60° cathedral ceiling canopy

* Unipack is not available for 72" blade option

Blade Options





CEILING PITCH TABLE

0/12	0 degrees
1/12	4.76 degrees
2/12	9.46 degrees
3/12	14.04 degrees
4/12	18.43 degrees
5/12	22.62 degrees
6/12	26.57 degrees
7/12	30.26 degrees
8/12	33.69 degrees
9/12	36.87 degrees
10/12	39.81 degrees
11/12	42.51 degrees

CEILING HEIGHT / DOWNROD TABLE

Ceiling Height	Downrod Lengths <i>Field cuttable. Non-threaded</i>
10 ft or less	5 inches / 13 cm <i>Use safety cages if applicable</i>
10 -12 feet	10 inches / 25 cm
13 feet	20 inches / 51 cm
14 feet	30 inches / 76 cm
15 feet	48 inches / 122 cm
16 feet +	72 inches / 183 cm

Matthews Fan Company

1881 Industrial Drive
Libertyville, IL 60048
Tele: 847.680.9043
Fax: 847.680.8140
www.matthewsfanco.com

© 2023 Matthews Fan Company. All rights reserved.

